MB2000-5

File Number: E80533

UL Product **iQ**[™]

Yellow Card® c Sus



COMPANY

Mar-Bal Inc 787 Renaissance Parkway Painesville, OH 44077 United States

MODEL INFO

MB2000-5

Unsaturated Polyester (UP), glass reinforced, furnished as bulk

FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability (1.5 mm, Color: ALL)	V-0	ANSI/UL 94
ISO/IEC FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability (1.5 mm, Color: ALL)	V-0	IEC 60695-11-10
ELECTRICAL PROPERTIES	VALUE	TEST METHOD
Hot-wire Ignition (HWI) (1.5 mm)	PLC 0	UL 746A
High Amp Arc Ignition (HAI) (1.5 mm)	PLC 0	UL 746A
Comparative Tracking Index (CTI)	PLC 1	UL 746A
Dielectric Strength	17 kV/mm	ASTM D149
High Voltage Arc Tracking Rate (HVTR)	PLC 0	

21 MB2	2000-5 UL Product iQ	
Volume Resistivity	1.0E+14 ohms⋅cm	ASTM D257/IEC 60093
High Voltage, Low Current Arc Resistance	PLC 3	
THERMAL PROPERTIES	VALUE	TEST METHOD
Relative Thermal Index - Electrical Strength		UL 746B
1.5 mm	130 °C	
3.0 mm	130 °C	
Relative Thermal Index - Mechanical Impact		UL 746B
1.5 mm	130 °C	
3.0 mm	130 °C	
Relative Thermal Index - Mechanical Strength		UL 746B
1.5 mm	130 °C	
3.0 mm	130 °C	
PHYSICAL PROPERTIES	VALUE	TEST METHOD
Dimensional Stability	0.0 %	ASTM D1042/ISO 2796
		Report Date: 1981-09-21 Revision Date: 2003-10-24

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"